F&B Diverclean Easyfoam VF32

Chlorine-based foamed detergent

Description

Easyfoam is a high foaming, chlorinated liquid detergent designed for generalpurpose cleaning in the food, beverage and dairy industries.

Key properties


- Easyfoam contains a blend of caustic alkali, hypochlorite and a high foaming wetting agent/emulsifier. It is effective for the removal of most food soils including animal and vegetable fats, blood and proteins. In addition, the presence of hypochlorite assists removal of organic and vegetable-based stains and helps to prevent build-up of 'protein film' deposits.
- Easyfoam is recommended for daily cleaning in vegetable processing, canning, wine and soft drink production. It is also suitable for use in abattoirs, poultry processors and the fish industry. It can be used for cleaning floors, walls, cutting tables, packing conveyors and other processing equipment.
- Easyfoam is suitable for use with a wide range of foam application equipment.

Benefits

- Cost-effective cleaner
- Effective on most types of food soiling
- Assists stain removal
- Free rinsing

Use instructions

Use Easyfoam at concentrations between 2-10% v/v depending on the type and degree of soiling.



F&B Diverclean Easyfoam VF32

Technical data

Appearance: Clear, pale yellow liquid
pH (1% solution at 20°C): 12.6
Relative density (20°C): 1.16
Chemical Oxygen Demand (COD): 80,1 gO2/kg
Nitrogen Content (N): 1 g/kg
Phosphorous Content (P): None
The above data is typical of normal production and should not be taken as a specification.

Safe handling and storage information

Store in original closed containers, away from sunlight and extremes of temperatures.
Full guidance on the handling and disposal of this product is provided in a separate Safety Data Sheet.

Product compatibility

Easyfoam when applied at the recommended concentration and temperature is suitable for use on the grades of stainless steel commonly found in the processed food industry. It is unsuitable for use on soft metals such as aluminium and galvanised materials. Always rinse surfaces thoroughly after use (within 1 hour).
In the event of uncertainty it is advisable to evaluate individual materials before any prolonged use.

Test method

Reagents:

0.1 N Hydrochloric or sulphuric acid
0.1 N Sodium thiosulphate
Phenolphthalein indicator

Procedure:

Add 10ml of 0.1N sodium thiosulphate to 10ml of the test solution, mix well and allow to stand for about 30 seconds, add 2-3 drops of the indicator solution and titrate with the acid to a colourless end point.

Calculation:

% v/v Easyfoam = titre (ml) x 0.4
% w/v Easyfoam = titre (ml) x 0.45
% w/w Easyfoam = titre (ml) x 0.45

© 2019 Diversey, Inc. All Rights Reserved. P00259 en 02/19